

# DELTA SERVAL

High-performance server

High-performance dual-socket general-purpose server based on the latest Intel® Xeon® 6 processors

Delta Serval is designed to work with resource-intensive application software, such as high-load ERP systems, business analytics systems, and HPC clusters



## Features:

- ▶ Up to 172 productive Granite Rapids-SP P-cores or 288 energy-efficient Sierra Forest-SP E-cores
- ▶ Hybrid system Delta Hybrid Cooling for maximum CPU time in Max Turbo Boost mode
- ▶ Up to 8 TB of DDR5 RAM at up to 6400 MT/s
- ▶ Up to 8 x 7mm U2 PCIe Gen5 NVMe SSDs
- ▶ Extensive monitoring and control functionality in the Delta BMC system
- ▶ Capability to install up to 5 high-speed PCIe Gen5 adapters
- ▶ Supports MCR DIMM memory with speeds up to 8000 MT/s
- ▶ 2x M2 PCIe NVMe for OS

|  |   |
|--|---|
| Processor socket                       | LGA 4710  |
| Processor                              | 2x Intel® Xeon® 6 Granite Rapids-SP, up to 350Bt<br>or<br>2x Intel® Xeon® 6 Sierra Forest-SP, up to 330Bt   |
| RAM                                    | Up to 32 DDR5 DIMMs up to 6400 MT/s   |
| Storage                                | Up to 2x SSD M2.2280 PCIe NVMe<br>Up to 8x SSD 2,5" U.2 7mm PCIe Gen5 NVMe<br>or<br>Up to 4x SSD 2,5" U.2 15mm PCIe Gen5 NVMe   |
| Внешние слоты                          | 1x PCIe Gen5 OCP 3.0<br>4x PCIe Gen5 x16 HHHL   |
| Внутренние слоты                       | 1x M2.2230 Key-E (Trusted Boot Module)  |
| External connectors on the front panel | 1x USB-A 3.0<br>1x miniDP<br>1x RJ-45 Gigabit Ethernet 10/100/1000 Mbit/s (Remote connection capability to the control system (Delta BMC) and operating system via a single port) |
| External slots                         | Delta Hybrid Cooling<br>N+1 cooling fan redundancy with hot-swap support  |
| Power supply                           | From centralized OCP busbar, 12V  |
| Embedded software                      | Delta BIOS<br>Delta BMC   |
| Device size type                       | 21" 2OU,  |
| Assembled weight                       | Up to 9,6 kg  |

# Appearance:



15mm U.2 NVMe drives  
(optional)

PCIe Gen5 expansion slots

7mm U.2 NVMe drives  
(optional)

USB-A 3.0

RJ45 connector

MiniVGA connector

OC3.0 network card slot (Mezz)

# Other products:

